

# VIDEO CONFERENCE CAMERA

## INVC10



USB2.0 HD Interface  
 HD 1080P  
 2.1 Mega Pixels  
 10X Zoom  
 Pan:0~360°  
 Tilt:+/-60° RS-232 RS-422 RS-485  
 IR Remote Control

|                            |   |                    |
|----------------------------|---|--------------------|
| Product Model              | INVC10  |                    |
| Image sensor               | Sensor  | 1/3" HD color CMOS |
|                            | Effective pixels  | 2.1 mega pixels    |
|                            | Minimum Illumination  | 0.5Lux at F2.0     |
|                            | White Balance   | Auto/Manual        |
|                            | Gain Control  | Auto               |
|                            | Backlight Compensation  | On/Off             |
|                            | S/N Ratio   | >50db              |
| Lens                       | Focal length  | f=4.9-49mm         |
|                            | Aperture  | Auto/Manual        |
|                            | Zoom  | 10X zoom           |
|                            | Horizontal angle of view  | 48.4°              |
| Video Output               | USB2.0  |                    |
| Signal System              | 1080P(1720P (1280x720) VGA(640x480) CIF(352x288)  |                    |
| Control Terminal           | USB,RS232C,RS485(Bidirectional)   |                    |
| Control Protocol           | VISCA, PELCO-D  |                    |
| Baud Rate                  | 9600/38400bps   |                    |
| Cruise Line                | 4 Lines   |                    |
| Pre-set Position           | 64  |                    |
| Image Flip                 | Support Horizontal/Vertical image flip  |                    |
| Pan Movement Speed         | 1-280°/S  |                    |
| Tilt Movement Speed        | 1-100°/S  |                    |
| Pan Movement Range         | 360°  |                    |
| Tilt Movement Range        | Up: 90°, Down: 45°  |                    |
| Pan Scanning Automatically | support   |                    |
| Boundary Scan              | 0-359°  |                    |
| Remote Control             | IR Wireless remote control P/T  |                    |
| Power Supply               | DC12V±10%,1.2A  |                    |
| Work Temperature           | 0-50°C  |                    |
| Work Humidity              | 0-95% RH  |                    |
| Dimension(LXWXH)           | 240 x 95 x 145mm/<br>330 x 285 x 130mm (before/after packing)   |                    |
| Weight:                    | 740g/1.8kg (before/after packing)   |                    |
| Accessories                | DC 12V power adapter, IR remote control, manual, RS-232C serial control line, USB2.0 cable (5 meters), Brackets & screws. |                    |
| Color                      | Silver Grey   |                    |